

AUTOLUBE AUTOMATIC TRANSMISSION FLUID (ATF)

SPECIAL PURPOSE HEAVY DUTY TRANSMISSION FLUID DESIGNED FOR SPECIFIC AUTOMATIC AND POWER SHIFT TRANSMISSIONS AS WELL AS FOR POWER STEERING SYSTEM APPLICATION.

APPLICATION

- AUTOMOTIVE HEAVY-DUTY AUTOMATIC TRANSMISSIONS ■ POWER STEERING
- SCREW TYPE AIR COMPRESSOR

PERFORMANCE LEVEL

MEETS OR EXCEEDS:

- DEXRON® IID AND IIID
- MERCON
- DENISON HF-0
- ALLISON C-4
- CAT TO-2
- VICKERS M-2950-S

BENEFITS

- EXCELLENT ANTI WEAR PROPERTIES ENSURE **LONGER EQUIPMENT LIFE.**

TYPICAL PHYSICAL CHARACTERISTICS	ATF
DENSITY @ 20°C KG/L	0.8664
VISCOSITY cST @ 40°C	36.5
VISCOSITY cST @ 100°C	7.2
VISCOSITY INDEX	165
POUR POINT °C (MAX)	-42
FLASH POINT °C (MIN)	193
VIS. BROOKFIELD cP @ 40°C	45,000
BORON, WT %	0.013
SULFUR, WT %	0.07
PHOSPHORUS, WT %	0.03

RE: 2001/11/01